



## Characteristics

Good adhesion between 18-22 degrees. Not suitable for freezing or rather cold environment. Suitable for boxes made from recycled paper.

Data		
Adhesion	High initial tack and does not roll off too lightly	
Sound	Noiseless	
Warranty	positive printing	1 year
	Bleed diapositive printed / coloured	Due to risk of tearing warranty can not be given
Max. width printing	Tape width minus 2 mm	
Colours	Clear, white	
Number of colours printed	Up to 5 colours and full colour spot	
Core diameter	76 mm	
Minimum order (50 mm x 66 mtr)	1 box = 24 rolls	

Tape material	Tapewidth in mm. From ■ in maximum length possible												Max. length	Max. number of colours	Thickness foil
PVC	9	12	15	19	25	30	38	50	75	-	150	200	660 mtr	5	60 $\mu$

## Application

PVC 60 $\mu$  is a self-adhesive packaging tape with a high tensile strength suitable for printing. The special adhesive and the thick backing material will ensure a reliable sealing of heavy cartons and pack lots.

Technical Data	Unit	
Base		Rigid PVC film
Adhesive		Natural rubber
Breaking Load	N/25mm N/cm	minimum 220 minimum 88
Thickness	mm	0.083 $\pm$ 10%
Adhesion Strength	cN/25mm N/cm	500 $\pm$ 150 2.0 $\pm$ 0.6

## Properties

- high tensile strength and adhesion strength
- moisture resistant
- resistant to diluted acids and alkalies
- heat resistant for short exposure up to about +70° C
- low temperature resistant down to about -20° C after application at room temperature
- suitable for printing